UL Product iQ™



GVEV.R13255 - SWINGING FIRE DOOR CLOSERS

Swinging Fire Door Closers

See General Information for Swinging Fire Door Closers

ASSA ABLOY KOREA CO LTD SAMHWA PRECISION

R13255

234 HUIMANGGONGWON-RO

SIHEUNG-SI, GYEONGGI-DO 15083 REPUBLIC OF KOREA

For self-closing doors, overhead concealed type, without hold-open feature, adjustable, size 2-3 Model(s) 300, 300A, 300JO, 300K, 300PT, 300S, 300VO, 310, 310-20-A-DP, 310-20-A-DPA, 310-20-A-DPJO, 310-20-A-DPK, 310-20-A-DPPT, 310-20-A-DPS, 310-20-A-DPVO, 310A, 310JO, 310K, 310PT, 310S, 310VO, 311, 311-20-A-DP, 311-20-A-DPA, 311-20-A-DPJO, 311-20-A-DPJO, 311-20-A-DPJO, 311-20-A-DPK, 311-20-A-DPPT, 311-20-A-DPS, 311-20-A-DPVO, 311A, 311JO, 311K, 311PT, 311S, 311VO, 312, 312A, 312JO, 312K, 312PT, 312S, 312VO, 313, 313A, 313JO, 313K, 313PT, 313S, 313VO, 500, 500A, 500JO, 500K, 500PT, 500S, 500VO, 510, 510A, 510JO, 510K, 510PT, 510S, 510VO, 511, 511A, 511JO, 511K, 511PT, 511S, 511VO, 512, 512A, 512JO, 512K, 512PT, 512S, 512VO, 513, 513A, 513JO, 513K, 513PT, 513S, 513VO

For self-closing doors, overhead concealed type, without hold-open feature, fixed, size 2 "200 Series" Model(s) 200, 200A, 200JO, 200K, 200PT, 200S, 200VO, 201, 201A, 201JO, 201K, 201PT, 201S, 201VO, 202, 202A, 202JO, 202K, 202PT, 202S, 202VO, 203A, 203JO, 203K, 203PT, 203S, 203VO, 220, 220A, 220JO, 220K, 220PT, 220S, 220VO, 221, 221A, 221JO, 221K, 221PT, 221S, 221VO, 222, 222A, 222JO, 222K, 222PT, 222S, 222VO, 223, 223A, 223JO, 223K, 223PT, 223S, 223VO

For self-closing doors, overhead concealed type, without hold-open feature, fixed, size 3 Model(s) 210, 210A, 210JO, 210K, 210PT, 210S, 210VO, 211, 211A, 211JO, 211K, 211PT, 211S, 211VO, 212, 212A, 212JO, 212K, 212PT, 212S, 212VO, 213, 213A, 213JO, 213K, 213PT, 213S, 213VO, 230, 230A, 230JO, 230K, 230PT, 230S, 230VO, 231, 231A, 231JO, 231K, 231PT, 231S, 231VO, 232, 232A, 232JO, 232K, 232PT, 232S, 232VO, 233, 233A, 233JO, 233K, 233PT, 233S, 233VO

For self-closing doors, overhead concealed type, without hold-open feature, fixed, size 4 Model(s) 240, 240A, 240JO, 240K, 240PT, 240S, 240VO, 241, 241A, 241JO, 241K, 241PT, 241S, 241VO, 242, 242A, 242JO, 242K, 242PT, 242S, 242VO, 243, 243A, 243JO, 243K, 243PT, 243S, 243VO

For self-closing doors, without hold-open feature, surface mounted regular, size 3 Model(s) KCD34 (size 3)

Swinging door closers for self-closing doors, without hold-open feature, overhead concealed type Model(s) K540

Investigated to Standard UL 10C.

For self-closing doors, concealed type, without hold-open feature, adjustable size 3-6 Model(s) DC490, may have prefix ST or DC, may be followed by suffix -P, -BC, -DA, -HO or -HO-P.

ST80P, may have prefix ST or DC, may be followed by suffix -P, -BC, -DA, -HO or -HO-P.

For self-closing doors, concealed type, without hold-open feature, size 2 Model(s) ST75 EN2, may have prefix ST or DC, may be followed by suffix -P, -BC, -DA, -HO or -HO-P.

For self-closing doors, concealed type, without hold-open feature, size 3 Model(s) ST75 EN3, may have prefix ST or DC, may be followed by suffix -P, -BC, -DA, -HO or -HO-P.

For self-closing doors, concealed type, without hold-open feature, size 4 Model(s) ST84, may have prefix ST or DC, may be followed by suffix -P, -BC, -DA, -HO or -HO-P.

For self-closing doors, concealed type, without hold-open feature, size 5 Model(s) ST85, may have prefix ST or DC, may be followed by suffix -P, -BC, -DA, -HO or -HO-P.

For self-closing doors, concealed type, without hold-open feature, size 6 Model(s) ST86, may have prefix ST or DC, may be followed by suffix -P, -BC, -DA, -HO or -HO-P.

For self-closing doors, surface mounted regular or parallel type, without hold-open feature, adjustable size 2-5 Model(s) D660, D660-P, D660BCP, D660BCP, D660DAP, D661DAP, D661-P, D661BCP, D661BCP, D661DA, D661DAP, D770-P, D770BCP, D770BCP, D770DAP, D770DAP, D771-P, D771BC, D771BCP, D771DAP, K900, K900-P, K900BC, K900BC BF, K900BC BF DA, K900BC BF P, K900BC DA, K900BC P

For self-closing doors, surface mounted regular or parallel type, without hold-open feature, size 2 Model(s) 620, 620-P, 620BC, 620BCP, D620, D620-P, D620BC, D620BC-P, D71, D71-P, D71BC, D71BCP, D72, D72-P, D720, D720-P, D720BC, D720BCP, D72BC, D72BCP, NX720, NX720-P, NX720BC, NX720BCP

For self-closing doors, surface mounted regular or parallel type, without hold-open feature, size 3 Model(s) 630, 630-P, 630BC, 630BCP, D630, D630-P, D630BC, D630BC-P, D73, D73-P, D730, D730-P, D730BCP, D730BCP, D73BC, D73BCP, NX730, NX730-P, NX730BC, NX730BCP

For self-closing doors, surface mounted regular or parallel type, without hold-open feature, size 4 Model(s) D640, D640-P, D640BC, D640BC-P, D74, D74-P, D740, D740-P, D740BC, D740BCP, D74BC, D74BCP

For self-closing doors, surface mounted regular or parallel type, without hold-open feature, size 5 Model(s) D650, D650-P, D650BC-P, D750BC-P, D750BC, D750BCP

For self-closing doors, without hold-open feature, surface mounted regular or parallel type "200 and 990 Series" Model (s) 200 (sizes 1, 2, 3, 4, 5 and 6), 990 (sizes 1, 2, 3, 4, 5 and 6), may have prefix K, D, NSK, or QDC, maybe followed by suffix -P, BC or BC-P, DA, DA-P, BC.DA or BC.DA-P.

For self-closing doors, without hold-open feature, surface mounted regular or parallel type Model(s) 300 (size 1-6), 600 (size 1-6), 640 (size 4), 650 (size 5), 700 (size 1-6), 740 (size 4), 750 (size 5), 800 (size 1-6), 840 (size 4), 850 (size 5), may have prefix K or D, may be followed by suffix -P, BC, or BC-P; only models 640, 650, 840, and 850 may have prefix K, D, QDC or NKS, may be followed by suffix P, BC, BC-P, DA, DA-P, BC.DA or BC.DA-P.

610 (size 2), 620 (size 2), 630 (size 3), 720 (size 2), 730 (size 3), 820 (size 2), 830 (size 3), may have prefix K or D, may be followed by suffix -P, -BC or -BC-P, only models 630, 820, 830 may have prefix or suffix K, D or NSK, may be followed by P, BC, or BC-P.

NSK 620, NSK 620-P

For self-closing doors, without hold-open feature, surface mounted regular or parallel type, adjustable size 2-6 Model(s) NK5051BF, NK5051BFBC, NK5051BFBC-DA, NK5051BFDA

For self-closing doors, without hold-open feature, surface mounted regular or parallel type, size 1, 2, 3, 4, 5 and 6 Model(s) NK4041, NK4041-P, NK4041BC, NK4041BC-P, NK5051, NK5051BC, NK5051BC-DA, NK5051DA

For self-closing doors, without hold-open feature, surface mounted regular or parallel type, size 2, 3 and 4 "70 Series" Model(s) 72, 73, 74, may have prefix K or D, may be followed by suffix -P, BC or BC-P.

For self-closing doors, without hold-open feature, surface mounted regular or parallel type, size 2, 3 and 4 "90 Series" Model(s) 90, may have prefix K, may be followed by suffix -P, BC or BC-P.

For self-closing doors, without hold-open feature, surface mounted regular or parallel type, size 2, 3, 4 and 5 "900 Series" Model(s) 900, may have prefix K or D, may be followed by suffix -P, BC or BC-P.

Last Updated on 2018-09-27

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions:

1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings).

2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"